Creating a local open source community

Presented To KWLUG

Tim Laurence   May 2020

The Problem

The Problem

- Many people in our community contribute to open source projects but but receive far too little recognition

The Problem

- Many people in our community contribute to open source projects but but receive far too little recognition

- Some may want to embark on a open source effort but lack role models and/or mentors

The Problem

- Many people in our community contribute to open source projects but but receive far too little recognition

- Some may want to embark on a open source effort but lack role models and/or mentors

- Many don't realize how many people contribute to open source

The Problem

- Many people in our community contribute to open source projects but but receive far too little recognition

- Some may want to embark on a open source effort but lack role models and/or mentors

- Many don't realize how many people contribute to open source

- People who help deserve some pride and recognition

My idea

My idea
Stickers!!!

My idea
Stickers!!!
For Laptops!!!

Why stickers?

Why stickers?

- Laptops love stickers.

Why stickers?

- Laptops love stickers.

- It is not pushy, people can casually learn a bit about each other and their communities

Why stickers?

- Laptops love stickers.

- It is not pushy, people can casually learn a bit about each other and their communities

- Spread via word of mouth is slow but strong

In practice

1. Someone who is affliated with the group meets people and after reasonable assurances they are a OS contributors, give them a sticker and registration code

2. Contributers register on a website so they can show off their sweet OS commits

3. And of course put the sticker on their laptop

TODO

1. Decide on a name and buy domain and get it hosted

2. Decide on a sticker design, (copyright and trademark)

3. Come up with a registration flow

4. Make a website

5. Get stickers printed

6. Register sticker distributers

7. Define Open Source (Use "Open Source Initiative" as standard? Don't limit to software)

1
```
+ | KW
- | COMMITS
```

2
```
+ | KW
- | COMMITS
```

3
```
+ | KW
- | COMMITS
```

4
```
+ | KW
- | COMMITS
```

5
```
+ | KW
- | COMMITS
```

6
```
+ | KW
- | COMMITS
```

7
```
+ | KW
- | COMMITS
```

8
```
+ | KW
- | COMMITS
```

10
```
      KW | +
COMMITS | -
```

11
```
- | KW
+ | COMMITS
```

12
```
±|KW COMMITS
```

13
```
±|KW
±|COMMITS
```

14
```
±|        KW
±|COMMITS
```

15
```
      KW|±
COMMITS|±
```

16
```
KW
COMMITS
```

17
```
± | KW COMMITS
```

18
```
+ |        KW
- | COMMITS
```